

## Truguard Microporous Gloss

### DESCRIPTION

Truguard Microporous Gloss provides a flexible and highly durable microporous high gloss finish which out-performs conventional gloss systems by up to two years. Truguard Microporous Gloss can be applied to suitably prepared exterior timber, metal and PVCu surfaces.

### USES

Particularly suitable for the long-term protection and decoration of exterior timber surfaces, when used in conjunction with Leyland Truguard Microporous Basecoat. Suitable for application to bare timber both softwood and hardwood and to surfaces which have been previously decorated with preservative woodstains.

### RECOMMENDED USES

Exterior.

### TYPE OF SUBSTRATE

Wood, metal and masonry surfaces.

### COLOUR RANGE

For colour availability, please refer to Leyland Trade Colour Range.

### FINISH

Gloss.

### COVERAGE

Approximately 15 square metres per litre depending on the nature and porosity of the surface being painted.

### DRYING TIME

Touch dry in 4-6 hours. Recoatable after 16-24 hours.

### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position.

**STORE AWAY FROM HEAT AND FLAME.**

### THINNER

White Spirit.

### PREPARATION

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Rub down sound glossy surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Treat any mould or lichen with sterilisation wash as directed. For maximum

performance, old paint or varnish should be completely removed. Treat new or bare surfaces with clear preservative, prime metal surfaces with an appropriate primer. Follow with a coat of Leyland Truguard Microporous Basecoat then two coats of Leyland Microporous Gloss. Special precautions should be taken during surface preparation off pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

### APPLICATION

Stir well before use. Apply two full coats, allowing 16 - 24 hours between coats under normal drying conditions.

### CLEANING

Remove as much product as possible from application equipment before washing. Replace lid firmly. Wash equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

### PRECAUTIONS

#### PAINT PRODUCT

#### FLAMMABLE

Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

Keep away from sources of ignition - No Smoking.

Ensure maximum ventilation during application and drying.

Avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner - **DO NOT USE SOLVENT OR THINNERS.**

When spraying, do not breathe spray, wear suitable respiratory protective equipment.

If swallowed seek medical advice immediately and show the container or label.

Keep out of reach of children.

### PROFESSIONAL DECORATORS

Safety data sheet available for professional user on request.

#### VOC CONTENT

HIGH VOC CONTENT 25-50%  
VOC's (Volatile Organic Compounds)  
contribute to atmospheric pollution.

Manufactured under a quality system approved by the BSI.

Issue Date: 03/02

Kalon Decorative Products, Huddersfield Road, Birstall, Batley, West Yorkshire. WF17 9XA.

Telephone: 01924 354000 Facsimile: 01924 354001