

## 1.10 Non Drip Gloss

### DESCRIPTION

An easy-to-use hardwearing, gloss finish which requires no undercoat. Ideal for use on interior and exterior wood and metalwork.



### Recommended uses

Interior ✓ Exterior ✓

### Type of substrate

Wood and metal.

### Colour range

Brilliant White.

### Finish

High Gloss

### Volume solid

61%

### Coverage

1 litre will cover approximately 14 square metres, depending on the nature and porosity of the surface. Strong or contrasting colours may require additional coats.

### Drying time

Touch dry in 2-4 hours. Recoatable after 16-24 hours.

### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.  
STORE AWAY FROM HEAT AND FLAME.

### Cleaner

White Spirit.

### VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 400 g/l (2007) / 300 g/l (2010). This product contains max 300 g/l VOC.

### Film thickness

Wet: 70µm

Dry: 43µm

### Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Prime all new and bare surfaces with the appropriate Leyland Primer. Rub down sound previously painted surfaces with fine waterproof abrasive paper to provide a key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

### Application

Do not stir. The brush should be fully loaded for best results. Occasionally, a small amount of liquid may appear in the tin, if this is not used in the first brushful, remove excess. Apply paint evenly by brush and avoid overspreading. Allow to dry overnight before applying a second coat if required. Do not apply over polystyrene surfaces.

### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly after use.

### Precautions

PAINT PRODUCT  
FLAMMABLE

- Contains Cobalt bis(2-ethylhexanoate) and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- Restrict interior use to small surface areas such as doors, window frames and skirting boards. Not recommended for interior use on large surface areas – walls, floors or ceilings – or in confined spaces.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.

**PROFESSIONAL DECORATORS Safety data sheet available on request.**  
Manufactured under a quality system approved by the BSI.