

1.6 Acrylic Eggshell



DESCRIPTION

A quick drying, eggshell finish, manufactured from high quality pigments and tough acrylic resin. Suitable for wall and ceiling surfaces in most interior situations. Its low odour properties combined with ease of application and speed of drying allow the work to be completed with a minimum of disruption.

Recommended uses

Interior ✓ Exterior ✗

Type of substrate

Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

Colour range

Brilliant White, Magnolia and a range of ready mixed colours. Thousands of additional colours are available via the Leyland tinting system.

Finish

Mid-sheen

Volume solid

36%

Coverage

1 litre will cover approximately 12 square metres, depending on the nature and porosity of the surface. When using more than one tin of a colour in the same room, intermix before use.

Drying time

Touch dry in 1-2 hours. Recoatable after 3-4 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.
PROTECT FROM FROST.

Thinner

Clean water.

VOC content

LOW VOC CONTENT 0.3-7.99%
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a):
75 g/l (2007) / 30 g/l (2010).
This product contains max 10 g/l VOC.

Film thickness

Wet: 83µm
Dry: 30µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Remove all loose and defective paint. Rub down previously painted surfaces with fine waterproof abrasive to provide a good key. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Prime where required with appropriate Leyland Primer. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact Technical Advisory.

Application

Stir well before use. On absorbent surfaces, the first coat should be thinned when necessary to ease application, taking care not to over-thin. Suitable for application by brush, roller or spray. Apply two full coats, allowing 3-4 hours between coats under normal conditions. On certain surfaces a third coat may be necessary. For spray application, thin with clean water as required, using up to approximately 0.5 litres of water to 5 litres of paint. Do not apply when air or surface temperature is below 10°C. Conditions of high humidity can prolong the drying time.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use in warm, soapy water and rinse thoroughly. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Precautions

PAINT PRODUCT

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.

PROFESSIONAL DECORATORS Safety data sheet available on request.
Manufactured under a quality system approved by the BSI.