



3.2 Truguard Pliolite® Based Masonry



DESCRIPTION

Specially formulated on durable Pliolite® Resin, providing excellent adhesion to the substrate, eliminating the need for a separate stabilising primer and providing resistance to rain within 20 minutes of application. The smooth, durable, matt finish can be applied in temperatures as low as -5°C, enabling year-round application.

Recommended uses

Interior Exterior

Type of substrate

Concrete, cement rendering, brick, stone, blockwork and pebbledash.

Colour range

Brilliant White and a wide range of ready mixed colours.

Finish

Matt

Volume solid

49%

Coverage

1 litre will cover approximately 8 square metres on smooth surfaces. In common with all wall paints, the spreading rate will be reduced on rough and absorbent surfaces such as pebble dash. When using more than one tin of a colour, it is advised that you intermix the quantity required beforehand.

Drying time

Touch dry in 1-2 hours. Recoatable after 24 hours.

Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.

STORE AWAY FROM HEAT AND FLAME.

Cleaner

White Spirit.

VOC content

HIGH VOC CONTENT 25-50%

VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/c): 450 g/l (2007) / 430 g/l (2010). This product contains max 430 g/l VOC.

The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Leyland's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.

PROFESSIONAL DECORATORS Safety data sheet available on request.
Manufactured under a quality system approved by the BSI.

Film thickness

Wet: 125µm

Dry: 61µm

Preparation

Ensure surface to be painted is sound, clean, dry and free from grease. Treat any mould or lichen with Sterilisation Wash as directed. Chalky, underbound surfaces should be scraped, dry brushed and sealed with Leyland Truguard Stabilising Masonry Primer. Wear a suitable face mask if creating dust.

Application

Stir well before use. Do not thin. Apply two coats, allowing 16-24 hours between coats under normal conditions. Do not apply to surfaces which are to be overcoated with conventional undercoat and gloss paint. Suitable for application by brush, roller, conventional or airless spray.

Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with white spirit. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

Precautions

PAINT PRODUCT

- Contains Solvent naphtha light aromatic.
- Harmful to aquatic organisms.
- May cause long term adverse effects in the aquatic environment.
- Avoid release to the environment.

FLAMMABLE

- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.