

### 1.18 Heavy Duty Floor Paint



#### DESCRIPTION

A hard wearing, protective, satin finish. Based on polyurethane alkyd resins which have been designed to withstand spillage and repeated cleaning. Ideal for use on most concrete and wooden floor areas such as garages, warehouses, workshops and factories, where the application of two coats provide excellent durability.

#### Recommended uses

Interior ✓ Exterior ✗

#### Type of substrate

Concrete, and wooden floors. For further advice on other substrates contact Technical Advisory.

#### Colour range

A wide range of ready mixed colours. Also available in clear.

#### Finish

Mid-sheen

#### Volume solid

57%

#### Coverage

1 litre will cover approximately 11 square metres, depending on the nature and porosity of the surface.

#### Drying time

Touch dry in 3 hours. Recoatable after overnight drying. The coating is fully cured in 7 days.

#### Transportation and storage

To avoid the risk of spillage, always store and transport in a secure upright position.  
STORE AWAY FROM HEAT AND FLAME.

#### Cleaner

White Spirit.

#### VOC content

HIGH VOC CONTENT 25-50%  
VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/i): 600 g/l (2007) / 500 g/l (2010). This product contains max 450 g/l VOC.

#### Film thickness

Wet: 91µm  
Dry: 52µm

#### Preparation

Ensure all floor surfaces to be painted are sound, clean, dry and completely free from oil, grease and polish. New concrete floors should preferably be allowed to mature for several months before painting and the moisture content should be checked before work commences. Concrete surfaces should also be free of dust, grit, cement fines and laitance. Very dense smooth concrete surfaces (such as power floated concrete) normally require to be acid etched before painting in order to promote satisfactory adhesion.

#### Application

Stir well before use. Apply two coats, allowing overnight drying between coats under normal drying conditions. Where necessary, to ease application, the first coat may be thinned with up to 5% by volume of White Spirit. Apply by brush or roller.

#### Cleaning

Remove as much product as possible from application equipment before cleaning. Clean equipment immediately after use with White Spirit or Turpentine Substitute. Some local authorities have special facilities for disposal of waste coatings. Do not empty product into drains or watercourses. Replace lid firmly.

#### Precautions

PAINT PRODUCT  
FLAMMABLE

- Contains Cobalt Carboxylate and Ethyl Methyl Ketoxime. May produce an allergic reaction.
- Repeated exposure may cause skin dryness or cracking.
- Keep away from sources of ignition – No smoking.
- Ensure maximum ventilation during application and drying.
- Avoid contact with skin and eyes. In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner – DO NOT USE SOLVENT OR THINNERS.
- When applying by brush or roller to large interior surfaces or in confined spaces, wear a suitable cartridge respirator or airfed respiratory protective equipment.
- If swallowed, seek medical advice immediately and show this container or label.
- Keep out of the reach of children.

**PROFESSIONAL DECORATORS Safety data sheet available on request.**  
Manufactured under a quality system approved by the BSI.